



Certificate of Compliance

Certificate: 1314504 (LR 102502-6)

Master Contract: 157759

Project: 1859351

Date Issued: 2007/01/11

Issued to: Turck Inc.

3000 Campus Dr
Plymouth, MN 55441-2656
USA
Attention: Mr. Paul Harms

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US'



Issued by: Bob Chippel, P. Eng.

Authorized by: Nick Alfano, Operations Manager

PRODUCTS

CLASS 6233 81 - RECEPTACLES - Attachment Plug Type and Plugs - Certified to US Standards

CLASS 6233 01 - RECEPTACLES - Attachment Plug Type and Plugs

Part A: VB series of 4-, 6- and 8-port junction boxes using I/O "EuroFast" series of special use male plugs and female connectors rated 4A max* per Port, 12A max* total, 48V dc max. * See Fig 2 for current ratings.

Part B: VBKB Series of 4-, 6- and 8-port junction boxes using "microfast" port connectors rated 4A* max per Port, 9A* max total, 250V ac max, 300V dc max. * See Fig 17 for current ratings.

Part C: RKF, RXF Series of 4-, 6- and 8-port junction boxes using "minifast" port connectors rated 4A* max

The 'C' and 'US' indicators adjacent to the CSA Mark signify that the product has been evaluated to the applicable CSA and ANSI/UL Standards, for use in Canada and the U.S., respectively. This 'US' indicator includes products eligible to bear the 'NRTL' indicator. NRTL, i.e. National Recognized Testing Laboratory, is a designation granted by the U.S. Occupational Safety and Health Administration (OSHA) to laboratories which have been recognized to perform certification to U.S. Standards.



Certificate: 1314504 (LR 102502-6)

Master Contract: 157759

Project: 1859351

Date Issued: 2007/01/11

per Port, 9A* max total, 250V ac max, 300V dc max. * See Fig 24 for current ratings. Alternate model number WDX19-80-XXXX.

Part D: RKF, RXF Series of 4- and 8-port junction boxes using “minifast” port connectors with LED indication, rated 4A* max per Port, 9A* max total, 40 to 120V ac max. * See Fig 33 for current ratings. Alternate model number WDX19-80-XXXX..

Part E: VBKB Series of 4- and 8-port junction boxes using “microfast” port connectors with LED indication, rated 4A* max per Port, 9A* max total, 40 to 120V ac max. * See Fig 37 for current ratings.

APPLICABLE REQUIREMENTS

CSA Std C22.2 No 21-95 - Cord Sets and Power Supply Cords

CSA Std C22.2 No 182.3-M1987 - Special Use Attachment Plugs, Receptacles, and Connectors

ANSI/UL Std No 817 - Cord Sets and Power Supply Cords

UL Std No 1977 - Component Connectors for Use in Data, Signal, Control and Power Applications