


BLU,PVC,9X22,ITC Instrumentation Tray Cable – Reelfast™ Bulk Cable



Features



- ITC 150V
- PLTC 300V
- UL/CSA AWM 300V
- CMX OUTDOOR 300V
- CMG 300V
- Instrumentation Tray Cable
- Blue PVC jacket, 9X22 AWG
- Sunlight Resistant
- -40 Cold Bend Rating
- Oil Resistant
- Flame Ratings: UL 1685 FT4, UL1061, CSA FT4

Technical data

Type	BLU,PVC,9X22,ITC
Ident. no.	RF50741
Cable	
Cable platform	Instrumentation tray cable
	9
Cable diameter	Ø 6.86 mm
Cable jacket	PVC, Blue
Conductor diameter	0.048 "
Conductor material	?
Core insulation	SR-PVC
Core cross-section	9 x 22 AWG [Similar to 0.34 mm ²]
Arrangement of strands	19 x 0.0058 "
Core colors	VT, YL, WH, BK, GN, RD, OG, BU, BN
Weight	0.16 lbs. /meter
Electrical properties at +20 °C	
Voltage	ITC 150V PLTC 300V UL/CSA AWM 300V CMX OUTDOOR 300V CMG 300V
Dielectric withstand (min.)	2 KVAC
DC resistance (max)	17.5 Ω/1000ft max.
Mechanical and chemical properties	
Bending radius (stationary installation)	≥ 5 x Ø
Bending radius (flexible use)	≥ 10 x Ø
Cold flexural strength	-40 °C
Stationary	-40 °C...+105 °C
In motion	-40 °C...+105 °C

Technical data

-20 °C...+105 °C

Approval	
UL Approvals	UL 2250 ITC UL 13 PLTC Sunlight Resistant -40C Cold Bend Oil Res I Oil Res II UL 758 AWM 2517
CSA Approvals	CSA AWM I/II A/B UL 444 CMX OUTDOOR-CMG CSA FT4
Cable compliances	RoHS
Note	
	- Flex values can be reduced when used in extreme temperatures, in contact with certain chemicals, above the nominal speed or below the nominal bending radius.
	- We reserve the right to make technical modifications without prior notice.