


Aktuator- und Sensor, konfektionierbar
M8 × 1 Female Connector, Straight
B 5133-0



Type	B 5133-0
ID	U0879-54
Connector A	Female, M8 × 1, Straight
Design specification	acc. to IEC 61076-2-104
Number of pins	3
Contact carriers	Plastic, PA 66 (UL 94 HB), Black
Connector body	Plastic, PBT, Black
Coupling nut/screw	Brass, CuZn, Nickel-plated
Seal	O ring, Plastic, FKM/FPM
Tightening torque (range)	0.4 ... 0.8 Nm (observe max. torque of mating connector!)
External diameter of the cable	3.5...5 mmmm
Core cross-section/Clamping ability	0.14...0.5 mm²
Core cross-section/terminal capacity	26...20 AWG
Connection mode	Screw/clamp connection
Mechanical lifespan	> 100 Mating cycles
Pollution degree	3
Protection class	IP67
	NEMA: 1, 3, 4, 6P
Electrical properties at +20 °C	
Rated voltage	60V _{AC} /75V _{DC}
Current	4AA
Mechanical and chemical properties	
Ambient temperature (fixed)	-40...+85°C
Note	
- We reserve the right to make technical modifications without prior notice.	

- M8 connection
- Rated voltage: 75 VDC 60 VAC
- M8 female connector, straight, 3-pin
- Plastic housing
- Protection class: NEMA 1, 3, 4, 6P, IEC IP67
- Screw terminal connection
- Plastic housing

