

# DEUTSCH DT-SERIES CONNECTORS WITH LED INDICATION



Turck's rugged 2-pin LED DT Series connectors deliver multidirectional troubleshooting to provide easy on-vehicle visual indication. Featuring bright red LEDs for both 12 VDC or 24 VDC systems and solid contact for long term durability.

### Product Highlights

- Red LED indicator
- Solid contacts
- Meets IEC IP67

### Cable Features


- 18 AWG Conductors
- Cut-Through and Abrasion resistant TPE
- Flexible and Oil Resistant
- Temperature range -40 to +105 °C
- Sunlight Resistant
- Cold Bend rated to -40 °C

Female	Application	Female	End View with Pinout
	2-wire 12 VDC LED indication	DT06-2S-2125-*M/LED12V	1. WH 2. BK
	2-wire 24 VDC LED indication	DT06-2S-2125-*M/LED24V	1. WH 2. BK

We reserve the right to make technical alterations without prior notice.

### Pinouts

#### Female 2-pin



\* Length in meters.

For other combinations or cable options, consult factory

# DEUTSCH DTM-SERIES CONNECTORS



Turck's Deutsch DTM Series connectors provide all the rugged benefits of an overmolded connector in a package designed for smaller AWG wires and lower current applications. Solid contacts provide long term performance in demanding environments.

### Product Highlights

- Solid Contacts
- Meets IEC IP67
- TPU connector body

### Cable Features

- 22 AWG Conductors
- Cut-Through and Abrasion resistant TPE
- Flexible and Oil Resistant
- Temperature range -40 to +105 °C
- Sunlight Resistant
- Cold Bend rated to -40 °C

Female	Male	Application	Female	Male	Extension	End View with Pinout
		3-wire	DTM06-3S-2303-*M	DTM04-3P-2303-*M	DTM06-3S-2303-*M- DTM04-3P	1.GN 2.BK 3.WH

### Pinouts

Female 3-pin	Male 3-pin

\* Length in meters.

For other combinations or cable options, consult factory

We reserve the right to make technical alterations without prior notice.